

SERIES 200

New Construction Double Hungs



STANDARD FEATURES

- 1. 2- 15/16" Multi-chambered Main Frame**
with Integral Nailing Fin & J-channel
- 2. Fusion Welded Vinyl Frame & Sash**
Corners never crack or pull apart
- 3. 3/4" Insulated Glass**
Double paned to reduce energy costs
- 4. PPG's Intercept Spacer System**
High Performing Warm Edge Technology
- 5. Constant Force Balance System**
Smooth, quiet operation
- 6. Die Cast Locks** (single lock if width under 24")
Secure locking action
- 7. Recessed Tilt Latches**
Clean appearance and easy cleaning
- 8. Full width steel reinforced lock rail**
Structurally strong and interlocks air tight
- 9. True Sloped Sill**
Effective water management
- 10. Aluminum Screen Frame**
Fiberglass mesh keeps pests out



OPTIONAL FEATURES

- | | |
|--------------------------|-----------------------|
| Tan Color | 2 & 3 Lite Sliders |
| IntelliGlass Low E Glass | Fixed Lites |
| ClimaGuard SPF | Architectural Shapes |
| | Factory Mullied Units |

PERFORMANCE VALUES

Operating Force	32 lbs.
Air Infiltration	.18 cfm / ft ²
Water Resistance	7.5 psf
Structural Test Pressure	37.5 psf
Deglazing	passed
Forced Entry Resistance	passed
Clear U-Value	.50
IntelliGlass LE U-Value	.33

Series 200 windows with any IntelliGlass High Performance Glazing package meet ENERGY STAR requirements for all areas of the USA.

