

# Series 900



## Projecting Windows

### STANDARD FEATURES

1. **3-1/4" Multi-chambered Main Frame**  
Strong, worry-free & thermally efficient
2. **Fusion Welded Vinyl Frame & Beveled Sash**  
Dimensional appearance looks great
3. **3/4" Insulated Glass**  
Double paned to reduce energy costs
4. **PPG's Intercept Spacer System**  
High Performing Warm Edge Technology
5. **Maximum Strength Operating Hardware**  
Smooth, strong, sag-free operation
6. **Multi-Point Locking System**  
Secure locking action with a single handle
7. **Full Opening Range**  
Casements open 90 degrees for cleaning
8. **Double Compression Seals**  
Stop air and water infiltration
9. **Color Matched Aluminum Screen Frame**  
Fiberglass mesh keeps pests out.



### OPTIONAL FEATURES

Tan Color	2 & 3 Lite Casement Models
IntelliGlass Low E Glass	1 & 3 Lite Awning Models
ClimaGuard SPF	Fixed Lites
Integral Nailing Fin	Factory Muller Units

### PERFORMANCE VALUES

Operating Force	32 lbs.
Air Infiltration	.03 cfm / ft <sup>2</sup>
Water Resistance	7.5 psf
Structural Test Pressure	50.0 psf
Deglazing	N/A
Forced Entry Resistance	Grade 10
Clear U-Value	.44
IntelliGlass LE U-Value	.29

Series 900 windows with any IntelliGlass High Performance Glazing package meet ENERGY STAR requirements for all areas of the USA.

